



Product Bulletin

GULFPRIDE[®] ADVANCED FUEL EFFICIENT SYNTHETIC BLEND MOTOR OILS

Gulfpride[®] Advanced Fuel Efficient Synthetic Blend Motor Oil employs a combination of premium quality Group II base oils, select synthetic lubricants and superior additive technology that provides a higher level of performance and quality. They offer superior protection in turbocharged and high-power, high-efficiency gasoline, propane, and natural gas engines in the latest model passenger car and light duty trucks.

FEATURES AND BENEFITS:

Gulfpride[®] Advanced Fuel Efficient Synthetic Blend Motor Oil meet or exceed the latest automotive manufacturers' requirements and are licensed for API Service SN (Resource Conserving) as well as ILSAC GF-5. **SAE 5W-20, SAE 5W-30 and SAE 10W-30 Engine Oils** are premium multi-grade motor oils formulated to provide excellent all weather engine protection.

- Excellent anti-wear properties
- Improved fuel economy and durability
- Completely compatible with conventional motor oils
- Excellent shear stability and highly resistant to foaming
- Outstanding low-temperature fluidity and protection at start up

APPLICATIONS:

Gulfpride[®] Advanced Fuel Efficient Synthetic Blend Motor Oils are designed for today's higher revving, hotter running engines. SAE 5W-20 meets Ford's latest performance standard WSS-M2C945-A. SAE 5W-30 meets Ford's performance standard WSS-M2C946-A.

Gulfpride[®] Advanced Fuel Efficient Synthetic Blend Motor Oils meet or exceed the requirements of:

- ILSAC GF-5/API Service SN (Resource Conserving)
- All viscosities grades are licensed for API SN and are backward compatible with prior service categories (SM, SL, SJ, and SH).
- Most turbo-charged gasoline passenger car engines

Approvals / Recommended For Use:


API SN / ILSAC GF-5	5W-20	5W-30	10W-30
Ford WSS-M2C945-A	5W-20	-	-
Ford WSS-M2C946-A	-	5W-30	-
Chrysler MS-6395	5W-20	5W-30	10W-30
GM 6094**		5W-30	10W-30

** Obsolete Spec

06/16

NU-TIER BRANDS, INC.

UNDER LICENSE FROM GULF OIL LP • TULSA, OK 74133 • Phone 918-550-8026 • www.gulflubricants.net or www.Nu-Tierbrands.com



Typical Properties

SAE Grade		5W-20	5W-30	10W-30
Product Code	Test Method	330132	330133	330136
Gravity, API	ASTM D-4052	33.2	32.6	30.8
Density, lbs/gal (g/L)	Calculated	7.17 (859)	7.18 (860)	7.26 (870)
Viscosity, cSt @ 40°C	ASTM D-445	51.6	62.5	70
Viscosity, cSt @ 100°C	ASTM D-445	8.9	10.8	11
Viscosity Index	ASTM D-2270	158	157	146
CCS @ -25°C, cP	ASTM D-5293	----	----	5800
CCS @ -30°C, cP	ASTM D-5293	5400	5800	----
Color	ASTM D-1500	3.0	3.0	3.0
Pour Point, °C (°F)	ASTM D-5949	-48 (-54.4)	-45 (-49)	-36 (-32.8)
Flash Point, COC, °F/ (°C)	ASTM D-92	420 (216)	430 (221)	430 (221)
Highest API/ILSAC Performance		SN / GF-5	SN / GF-5	SN / GF-5

AVAILABILITY:

Gulfpride® Advanced Fuel Efficient Synthetic Blend Motor Oils are available throughout Gulf's marketing area. Your Gulf representative can provide specific information. Need additional information? Call Gulf @ 1-800-566-GULF or visit Nu-tierbrands.com.