



265 Jefferson Avenue • Cleveland, Ohio 44113-2594  
(216) 771-4300 • Ohio WATS (800) 362-1530  
Fax (216) 771-1845

Product Information

Page 1 of 1

## EL OIL

### Product Description

**EL Oil** is a multi-purpose, water emulsifiable cutting oil. The product is designed for medium to severe metalworking operations on a variety of metals, including stainless steels. The product combines sulfur, chlorine and fatty additives to provide strong anti-weld and extreme pressure properties. **EL Oil** can be used neat or diluted with water to the desired concentration. The product is easily removed by all conventional cleaning methods including alkali baths, dip tanks and vapor degreasing and will not interfere in subsequent operations on the workpiece.

### Benefits

- Suitable for a wide variety of operations on ferrous metals.
- Easily removed by conventional cleaning methods.
- Excellent interim rust protection.
- Outstanding Finish.
- High Film Strength.
- Good Tool Life.

### Typical Specifications

Appearance	Clear/Dark
Viscosity cSt @ 100°F	53.8
Viscosity S.U.S. @ 100 °F	250
Flash Point, C.O.C.	320°F min.
Wt./Gal	7.8
Sulfur	present
Chlorine	present
Fat	present

Refer to Universal Oil's Material Safety Data Sheet (MSDS) **16 28 30** for additional information.

Universal Oil Item Number: **16 28 30**

The statements, technical information and recommendations contained herein are reliable, but given without warranty or guarantee of any kind. We assume no responsibility for loss, damage or expense, direct or consequential, arising out of the use of, or inability to use, our goods.