



265 Jefferson Avenue • Cleveland, Ohio 44113-2594
(216) 771-4300 • Ohio WATS (800) 362-1530
Fax (216) 771-1845

Product Information

Page 1 of 1

UNIVERSAL LIFE TEST OILS

Product Description **Universal Life Test Oil** series are inhibited paraffinic oils that are resistant to foaming, oxidation and thermal decomposition. The products are blended with paraffinic base stock that is free of asphaltic constituents, light in color, low odor levels, high viscosity index and contain trace amounts of sulfur and nitrogen.

Applications **Universal Life Test Oils** are blended to established viscosity specifications with an enhanced oxidation inhibitor package to provide long service life.

Benefits

- Excellent oxidation stability
- Low volatility
- High viscosity index
- High aniline point

Specifications

Typical Property	ASTM Test Method	Typical Results		
		32	68	68 NA
Viscosity cSt @ 40°C	D 445	29.1	54.8	54.8
Viscosity cSt @ 100°C	D 445	5.01	7.58	7.58
Viscosity Index (min.)	D 2270	90	90	90
Gravity, API	D 287	31.5	30.0	30.0
UO Item Number		16-21-26	16-21-28	16-21-29

Refer to Universal Oil's Material Safety Data Sheet (MSDS) 16-21-10 for additional information.