



265 Jefferson Avenue • Cleveland, Ohio 44113-2594
(216) 771-4300 • Ohio WATS (800) 362-1530
Fax (216) 771-1845

Product Information

Page 1 of 1

UNIVERSAL LUBRICATING OIL N 68 F

Product Description Universal Lubricating Oil N68F is a naphthenic base stock compounded with fatty oil to provide added lubricity.

Applications Universal Lubricating Oil N68F has excellent anti-rust qualities and is used to lubricate industrial equipment requiring compounded products.

- Benefits**
- Anti-Rust: Protects against rust and corrosion on steel and copper.
 - Low Temperature Fluidity: Extends the useful temperature operating range.
 - Water Separation (Demulsibility): Separates easily from water to minimize rust, filter blockage, and oil fluidity changes.

Typical Specifications

Specific Gravity @ 60° F	0.9126
Pounds Per Gallon	7.6
Viscosity	
@ 40°C, cSt	64.6
@ 100°F, SUS	334
Pour Point, Degrees F	-22°
Flash Point, Degrees F Min.	340
Fatty Oil	Present
Appearance	Clear/Light

Refer to Universal Oil's Material Safety Data Sheet (MSDS) **16 21 60** for additional information.
Universal Oil Item Number: **16 21 60**.

The statements, technical information and recommendations contained herein are reliable, but given without warranty or guarantee of any kind. We assume no responsibility for loss, damage or expense, direct or consequential, arising out of the use of, or inability to use, our goods.