



265 Jefferson Avenue • Cleveland, Ohio 44113-2594
(216) 771-4300 • Ohio WATS (800) 362-1530
Fax (216) 771-1845

Product Information

Page 1 of 1

UNIVERSAL MINERAL OILS

Product Description **Universal Mineral Oils** are paraffin neutral oils. Six viscosity grades offer a selection suitable for various process applications where high flash point paraffin oils are desired.

Applications **Universal Mineral Oils** are recommended for use in a wide range of applications such as:

- Flushing and cleaning oil
- Blending / Process Oil
- Dust control
- Bearing Lubrication

Typical Property	Typical Results						
	ISO Grade	P 15	22	32	68	150	460
Viscosity, cSt @ 40°C		15.0	19.3	28.9	65.8	146	482
SUS @ 100°F		77.4	114	157	334	752	2400
cSt @ 100°C		3.2	4.2	5.2	8.4	13.9	30.2
Viscosity Index, min.		90	95	95	95	95	93
Pour Point, °F		0	0	0	0	5	10
Flash Point, °F		370	415	425	430	445	570
Neut.No. mg KOH/g		.01	.01	.01	.01	.01	.02
Weight/Gallon		7.1	7.13	7.15	7.2	7.25	7.4

Universal Oil Item Number: 16-21-55 16-21-12 16-21-13 16-21-14 16-21-15 16-21-17

Refer to Universal Oil's Material Safety Data Sheet (MSDS) [16-03-01](#) for additional information.

The statements, technical information and recommendations contained herein are reliable, but given without warranty or guarantee of any kind. We assume no responsibility for loss, damage or expense, direct or consequential, arising out of the use of, or inability to use, our goods.