



265 Jefferson Avenue • Cleveland, Ohio 44113-2594
(216) 771-4300 • Ohio WATS (800) 362-1530
Fax (216) 771-1845

Product Information

Page 1 of 1

UNIVERSAL MINERAL SEAL OIL

Product Description **Universal Mineral Seal Oil** is a narrow distillation range low viscosity oil.

Applications **Universal Mineral Seal Oil** is recommended for use in a wide range of applications such as:

- Cutting Oil For Stone And Ceramics
- Glass Grinding Oil
- Diluent For Cutting Oil
- Machining Oil For Non-ferrous Metals
- Hi Flash Solvent
- Honing Oil

Typical Property	ASTM Test Method	Typical Results
Gravity API	D-4052	39
Viscosity, cSt @ 40°C	D-2161	4.4
SUS @ 100°F		40.9
Distillation Range	D-86	
Initial Boiling Point °F (°C)		520° (271°)
End Point °F (°C)		625° (326°)
Flash Point °F	D-92	285°
Pour Point °C	D-5949	-9°
Aniline Point °C	D-611	88.3°
Kauri Butanol Value	D-1133	22.5
Composition Vol. %	D-2549	
Aromatics		10
Olefins		5.6
Saturates		83.2
Visual		Clear & Bright

Universal Oil Item Number 16-20-08

Refer to Universal Oil's Material Safety Data Sheet (MSDS) 16-20-08 for additional information.