



265 Jefferson Avenue • Cleveland, Ohio 44113-2594  
(216) 771-4300 • Ohio WATS (800) 362-1530  
Fax (216) 771-1845

Product Information

Page 1 of 1

## UNIDRAW 500

**Product Description** **Unidraw 500** is a water emulsifiable drawing lubricant. The product does not contain nitrites, active sulfur or PCBs. The product is easily removed by all conventional cleaning methods including alkali baths, dip tanks and vapor degreasing and will not interfere in subsequent operations on the workpiece.

**Applications** **Unidraw 500** is designed for light to medium severity drawing and stamping operations on steel and aluminum.

**Benefits**

- Suitable for a wide variety of operations on ferrous or non-ferrous metals
- Excellent interim rust protection
- Easily removed by conventional cleaning methods

### Typical Specifications

<b>Viscosity SUS @ 100°F</b>	<b>1350</b>
<b>Viscosity cSt @ 100°F</b>	<b>292</b>
<b>Appearance</b>	<b>Clear/Amber</b>
<b>Flash Point, C.O.C.</b>	<b>330°F min.</b>
<b>Wt./Gal.</b>	<b>8.1</b>

Refer to Universal Oil's Material Safety Data Sheet (MSDS) 16 28 29 for additional information.  
Universal Oil Item Number: 16 28 29

*The statements, technical information and recommendations contained herein are reliable, but given without warranty or guarantee of any kind. We assume no responsibility for loss, damage or expense, direct or consequential, arising out of the use of, or inability to use, our goods.*