



265 Jefferson Avenue • Cleveland, Ohio 44113-2594  
(216) 771-4300 • Ohio WATS (800) 362-1530  
Fax (216) 771-1845

Product Information

Page 1 of 1

## UTILITY OILS

**Product Description** **Utility Oils** are built with a Group II mix paraffin base stock to yield a high Viscosity Index, straight grade, non-detergent mineral oil.

**Applications** **Utility Oils** are recommended for lubricating plain and anti-friction bearings and gears operating under low to moderate loads.

**Benefits**

- Non-detergent
- Excellent water separation
- High Viscosity Index
- Good oxidation stability

### Specifications

#### Typical Property

	SAE 30	SAE 50
ISO-VG	100	220
Gravity, API	28.9	28.5
Flash Point, °F Min.	410°	430°
Viscosity, SUS		
@ 100°F	487	1020
@ 210°F	65.8	96.5
Viscosity, cSt		
@ 40°C	105	220
@ 100°C	11.94	19.68
Viscosity Index Min.	90	90
Pour Point, °F	0°	10°
Specific Gravity @ 15.6°C (60°F)	0.882	0.884
Pounds Per U.S. Gallon @ 15.6°C (60°F)	7.35	7.36
UO Item Number	16-21-41	16-21-58

Refer to Universal Oil's Material Safety Data Sheet (MSDS) 16-03-01 for additional information.