



265 Jefferson Avenue • Cleveland, Ohio 44113-2594
(216) 771-4300 • Ohio WATS (800) 362-1530
Fax (216) 771-1845

Product Information

Page 1 of 2

UNIVERSAL MULTI-PURPOSE AUTOMATIC TRANSMISSION FLUID

Product Description **Universal MP Automatic Transmission Fluid** is a passenger car and light truck automatic transmission for most pre-2006 automatic transmissions built by General Motors, Ford Motor Company and other makes requiring a high performance, multi-purpose, power transmission fluid.

Applications **Universal MP Automatic Transmission Fluid** is recommended for vehicles manufactured by General Motors Corporation and Ford Motor Company transmissions. It is also recommended for transmissions, power steering systems and hydraulic systems requiring an Allison C-4. Always check your owner's manual to determine the proper automatic transmission fluid for your transmission.

Universal MP Automatic Transmission Fluid meets or exceeds the following specification requirements:

- General Motors
- Ford Motor
- Allison C4 Fluid/TES-389
- Denison P-46 Piston Pump
- Vickers Pump

Benefits **Universal Multi-Purpose Automatic Transmission Fluid** is formulated with base stocks and additives that provide oxidation and thermal stability, friction control, load-carrying ability, corrosion and wear protection. It helps protect against the formulation of deposits, sludge, varnish, foam and also:

- maintains friction control for smooth shift action
- is specially formulated to prevent shudder
- retains low temperature fluidity and high temperature stability for long operating periods
- protects automatic transmission fluid coolers from corrosion
- practically eliminates transmission overhauls due to sludge, corrosion, and wear

*Refer to Universal Oil's Material Safety Data Sheet (MSDS) 16 09 01 for additional information.
Universal Oil Item Number: 16 09 01*

The statements, technical information and recommendations contained herein are reliable, but given without warranty or guarantee of any kind. We assume no responsibility for loss, damage or expense, direct or consequential, arising out of the use of, or inability to use, our goods.

UNIVERSAL MULTI-PURPOSE AUTOMATIC TRANSMISSION FLUID

Typical Test Data

SAE Grade	10W
API Gravity	33.4
Viscosity, Kinematic	
cSt @ 40°C	33.4
cSt @ 100°C	7.1
Viscosity, Brookfield	
cP @ -40°C	17,000
Viscosity Index	176
Flash Point, °C (°F)	202 (396)
Pour Point, °C (°F)	-48 (-54)
Color	Red

Typical test data are average values only. Minor variations which do not affect performance are to be expected in normal manufacturing.

Universal Oil Order Item Number:	16-09-01
Universal Oil MSDS Number:	16-09-01

S:\user\han\DocPDS\ATF\ATF 03 15 07.doc