



265 Jefferson Avenue • Cleveland, Ohio 44113-2594  
(216) 771-4300 • Ohio WATS (800) 362-1530  
Fax (216) 771-1845

Product Information

Page 1 of 2

## UNIVERSAL UNI TRACK HYDRAULIC OIL

Multi-Purpose

All-Season

### Product Description

**Universal Uni Track Hydraulic Oil** is a premium transmission-hydraulic fluid recommended for the complex lubrication systems of modern tractors, including industrial models. In these systems, the same lubricant may serve the hydraulic system, torque converter, transmission, power take-off, differential, power steering, and wet brakes.

### Applications

**Universal Uni Track Hydraulic Oil** meets the following manufacturers specifications:

- **John Deere:** J20C, JD303
- **AGCO:** Improved power fluid 821XL
- **Massey Ferguson:** M1135, M1141, M1143
- **Oliver:** Type 55
- **Caterpillar:** TO-2, MTD
- **Kubota:** UDT
- **White Farm Equipment:** Q-1826
- **Ford New Holland:** ESN-M2C134-D, FNHA-2-C-201
- **Case IH:** JIC-143, 144, 145, MS1206, 127, 1209, 1210, (TCH)
- **Minneapolis-Moline:** Fluids
- **Renk:** Bus Automatic Transmission Fluid
- **International Harvester:** B6
- **Volvo:** WB 101

It also meets most other manufacturers' specifications for transmission-hydraulic fluid. It can be used for makeup or refill in almost all tractor hydrostatic, hydraulic, transmission, differential, and other systems involving common lube oil sumps.

### Benefits

**Universal Uni-Track Hydraulic** gives all-season protection. It flows readily at low temperatures due to its low-temperature viscosity and pour point, and yet retains its body at high temperatures due to a high viscosity index.

- Anti-foam
- Anti-wear
- Seal protection
- Controlled frictional characteristics
- Anti-rust
- Extreme pressure
- Oxidative and thermal stability

Refer to Universal Oil's Material Safety Data Sheet (MSDS) 16-11-01 for additional information.

## UNIVERSAL UNI TRACK HYDRAULIC OIL

### Specifications

#### Typical Property

Typical Property	ASTM Test Method	Typical Results
SAE Viscosity Grade		10W/20
Viscosity @ 210°F, cSt (SUS)	D 445, 2161	8.6 (54.5)
Viscosity @ 100°F, cSt (SUS)	D 445, 2161	56 (261)
Viscosity Index	D 2270	142
Flash Point, Deg. F	D 92	430°
Pour Point, Deg. F	D 97	-30°
Color	D 1500	5.5
Zinc, Wt. %	D 208	0.14
Timken OK Load, lb.	D 2780	30
Allison Power Steering Pump Test		Pass
Copper Strip Corrosion, 3 hrs. @ 300°F	D 130	1a
Foam Test	D 892	Pass
Oxidation Test, 100 hrs. @ 300°F		Pass
Water Sensitivity Test (Additive Separation)		Pass
UO Item Number		16-11-01
MSDS Number		16-11-01

05 17 10..S:\user\nan\doc\PDS98\Hydraulic\UniTrack.doc