



265 Jefferson Avenue • Cleveland, Ohio 44113-2594  
(216) 771-4300 • Ohio WATS (800) 362-1530  
Fax (216) 771-1845

*Product  
Information*

*Page 1 of 2*

## **Universal Unifleet LE HDMO SAE 15W40 CK-4, CJ-4, CI-4, CH-4/ SN, CI-4 Plus**

### **Product Description**

**Universal Unifleet LE HDMO SAE 15W40** is formulated for today's heavy duty engine applications and is an excellent choice for on-highway fleets, general haul, construction, agriculture, public-transport operators and diesel pick-up trucks. This includes high-power vehicles where resistance to increased heat and stress is required. It is fully API backwards compatible and it offers better performance than other CJ-4 lubricants due to enhanced protection against viscosity loss due to shear and improved oil aeration

### **OEM SPEC'S**

DFS 93K222, DFS 93K218, RLD-4, RLD-3, ECF-3, ECF-2, M3575, EOS-4.5, EO-O Premium Plus, EO-N, VDS-4.5, VDS-4, VDS-3, CES 20086, CES 20081, MB 228.31, MTU Category 2.1, E9-2012, E7, Ford WSS-M2C171-F1

### **Benefits**

- Suitable for use in older and newer engines with full back serviceability with API CJ-4 and most older engine oil qualities
- Exceptional wear performance and outstanding cylinder, bearing and ring wear results
- Enhanced performance and extended drain capability versus API CJ-4
- Improved oxidation protection and aeration control
- Outstanding cross-head and injector screw weight loss
- Excellent bore polish and cylinder wear results

**Specifications**

Typical Property	Typical Results
Viscosity @ 100°C, cSt	15.27
Viscosity @ 40°C, cSt	112.10
Viscosity Index	143
API Gravity at 60°F	30.6
Pour Point, °C	-36
Color ASTM	L3.5
CCS, cP	5,200 (-20c)
Flash Point COC, °C	232
TBN	10.2
Sulfated Ash, %m	0.91
Universal Oil Item No	160401