



265 Jefferson Avenue • Cleveland, Ohio 44113-2594
(216) 771-4300 • Ohio WATS (800) 362-1530
Fax (216) 771-1845

Page 1 of 1

*Product
Information*

UNIVERSAL MULTIPURPOSE D/M ATF

Product Description **UNIVERSAL MULTIPURPOSE D/M ATF** is formulated with selected Group II base oils and additives to provide excellent oxidation control and low temperature performance required in passenger car and light truck transmissions.

Applications It is recommended for use in all domestic and imported automatic transmissions produced prior to 2006 requiring GM Dexron III® or Ford Mercon® fluids

(a) Except for those that require Mercon V ATF, Dexron VI, CVT, Ford Type F, and under warranty Allison C-4.

(b) Do not use in Honda power steering fluid systems

(c) Consult your owner's manual regarding its suitability as ATF in imported vehicles.

The recommended shelf life for these oils is typically 48 months from manufacturing date when stored properly in the original sealed containers.

Specifications

Typical Property	Typical Results
Viscosity @ 100c, cSt	7.26 – 7.38
Viscosity @ 40c, cSt	35.15 – 35.67
Viscosity Index	177 - 179
Pour Point (C)	- 45 (C)
Brookfield Viscosity	17,300 – 18,500
Color	Red
Universal Oil Item No	160904