



265 Jefferson Avenue • Cleveland, Ohio 44113-2594
(216) 771-4300 • Ohio WATS (800) 362-1530
Fax (216) 771-1845

*Product
Information*

UNIVERSAL FULL SYN HD ATF

**Product
Description**

UNIVERSAL FULL SYN HD ATF offers extended friction control protection that lasts over the life of the fluid—long after the anti-shudder protection found in many competitive brands. Made with full synthetic base stocks, this ATF is inherently more thermally stable when compared with conventional base stocks.

Applications

UNIVERSAL FULL SYN HD ATF is designed for use in most heavy-duty applications. It also can be used in applications where its performance features exceed the requirements of older specifications.

Benefits

Full synthetic formula with outstanding low temperature performance

Provides extended anti-shudder performance for smooth driving

Improved wear performance and reduced oil consumption

Excellent oxidation and thermal stability

OEM Specs

Recommended for use in applications calling for:

Allison TES-295
Allison TES-389

This product is not OEM-approved under TES-295 or TES-389 certification. It is not officially licensed or approved by Ford or General Motors

Consult your owner's manual regarding its suitability as ATF in imported vehicles. Do not use in ATF applications where CVT fluids or Ford ATF type F is required. Do not use in Honda power steering fluid systems

Specifications

Typical Property	Typical Results
Viscosity @ 100°C, cSt	7.349 - 7.75
Viscosity @ 40°C, cSt	34.81 - 37.28
Viscosity Index	184
API Gravity	35.42 - 35.8
Pour Point, °C	-51
Brookfield @ -40°C, cP	8,000 - 12,000
Color	Red
Universal Oil Item No	160905