



265 Jefferson Avenue • Cleveland, Ohio 44113-2594
(216) 771-4300 • Ohio WATS (800) 362-1530
Fax (216) 771-1845

Product Information

Page 1 of 1

UNIVERSAL HD PRE-CHARGE ANTIFREEZE Concentrate and 50/50

Universal HD Pre-Charge Antifreeze protects heavy duty diesel wet sleeve liners and is based on a proprietary formulation of corrosion inhibitors. A traditional coolant ideally suited for older vehicles, classic is recommended for use where a fully formulated heavy duty diesel coolant is required.

Coolant concentrate must be diluted with water prior to use. Antifreeze/Coolant should not be used in concentrated form. A 50% dilution is generally recommended for the best balance of protection against freezing, corrosion and summer boil-over. For increased freeze protection in extremely cold areas, a 60% volume concentration can be used. Concentrations of greater than 70% by volume are not recommended. High quality soft, de-ionized or distilled water should always be used to dilute coolant concentrate.

When added as an initial fill and properly maintained in accordance with engine manufacturer's maintenance recommendation, this product will provide an in-service life of up to 250,000 miles/ 400,000 km, or 2 years, whichever comes first. While deleterious effects are not expected to be significant, mixing with conventional coolants will result in a lower than expected lifetime.

Product should be stored in original container or appropriate dedicated tank or vessel. Although temperature fluctuations will not adversely affect coolant, unused coolant should be stored at ambient conditions. Under typical conditions and when the container integrity is maintained, product can be stored for up to 2 years without any adverse effect on quality. Product should be agitated before use.

	Concentrate	50/50
Universal Oil Item Number:	16-42-01	16-42-02
Universal Oil MSDS Number	16-42-01	16-42-02

Always consult your vehicles owner manual for proper fluid recommendations and flushing procedures.

The statements, technical information and recommendations contained herein are reliable, but given without warranty or guarantee of any kind. We assume no responsibility for loss, damage or expense, direct or consequential, arising out of the use of, or inability to use, our goods.