



265 Jefferson Avenue • Cleveland, Ohio 44113-2594
(216) 771-4300 • Ohio WATS (800) 362-1530
Fax (216) 771-1845

Product Information

Page 1 of 1

UNIVERSAL HD NOAT EXTENDED LIFE ANTIFREEZE Concentrate & 50/50

Universal HD NOAT Extended Life Antifreeze provides up to 1,200,000 km, 750,000 miles, 15,000 hours or 8 years under normal operating conditions provided the coolant is kept in good condition with nitrite levels in line with the engine's OEM's requirements. Silicate-free provides for no possibility of silicate drop-out or gel formation.

Protects all coolant system metals against rust & corrosion, offering excellent aluminum & wet sleeve liner cavitation protection even at high temperatures. Being 2-EHA free, it is compatible with all system elastomeric materials ensuring optimal system performance.

OAT corrosion inhibitor system, is engineered for new cooling systems, offering protection against corrosion and deterioration, providing excellent high temperature aluminum and liner cavitation protection. This level of protection affords a lower overall operating costs compared to other coolants. HD Expert Extreme is Nitrite & Molybdate rich as well as being 2-EHA, Silicate, Borate, Amine & Phosphate free.

Coolant concentrate must be diluted with water prior to use. Antifreeze/Coolant should not be used in concentrated form. A 50% dilution is generally recommended for the best balance of protection against freezing, corrosion and summer boil-over. For increased freeze protection in extremely cold areas, a 60% volume concentration can be used. Concentrations of greater than 70% by volume are not recommended. High quality soft, de-ionized or distilled water should always be used to dilute coolant concentrate.

When added as an initial fill and properly maintained in accordance with engine manufacturer's maintenance recommendation, this product will provide an in-service life of up to 750,000 miles/1,200,000 km, 15,000 hours or 8 years, whichever comes first. While deleterious effects are not expected to be significant, mixing with conventional coolants will result in a lower than expected lifetime.

Product should be stored in original container or appropriate dedicated tank or vessel. Although temperature fluctuations will not adversely affect coolant, unused coolant should be stored at ambient conditions. Under typical conditions and when the container integrity is maintained, product can be stored for up to 2 years without any adverse effect on quality. Product should be agitated before use.

	Concentrate	50/50
Universal Oil MSDS / Item Number	16-42-09	16-42-10

Always consult your vehicles owner manual for proper fluid recommendations and flushing procedures.

The statements, technical information and recommendations contained herein are reliable, but given without warranty or guarantee of any kind. We assume no responsibility for loss, damage or expense, direct or consequential, arising out of the use of, or inability to use, our goods.