



265 Jefferson Avenue • Cleveland, Ohio 44113-2594
(216) 771-4300 • Ohio WATS (800) 362-1530
Fax (216) 771-1845

Product Information

Page 1 of 1

UNIVERSAL GLOBAL HEAVY DUTY EXTENDED LIFE ANTIFREEZE Concentrate & 50/50

Universal Global Heavy Duty Extended Life Antifreeze designed for complete “Mixed Fleet” use in all makes and models of passenger vehicles, light duty and heavy duty diesel vehicles including on-road, off road, construction, and farm applications. This nitrite-free product eliminates the need to carry multiple coolants to service different engines, providing for added value.

Provides up to 250,000 km, 150,000 miles, or 5 years (Automotive Light Duty); and up to 960,000 km, 600,000 miles, 12,000 hours or 6 years (Heavy Duty Diesel) under normal operating conditions provided the coolant is kept in good condition and in line with the engine’s OEM’s requirements.

OAT corrosion inhibitor system, is engineered for new cooling systems, offering protection against corrosion and deterioration, providing excellent high temperature aluminum and liner cavitation protection. This low silicate product is 2-EHA, Nitrite, Amine, Borate & Phosphate free.

Coolant concentrate must be diluted with water prior to use. Antifreeze/Coolant should not be used in concentrated form. A 50% dilution is generally recommended for the best balance of protection against freezing, corrosion and summer boil-over. For increased freeze protection in extremely cold areas, a 60% volume concentration can be used. Concentrations of greater than 70% by volume are not recommended. High quality soft, de-ionized, or distilled water should always be used to dilute coolant concentrate.

When added as an initial fill and properly maintained in accordance with engine manufacturer’s maintenance recommendation, this product will provide an in-service life of up to 250,000 km/150,000 miles or 5 years (Automotive Light Duty); 960,000 km/600,000 miles, 12,000 hours or 6 years (Heavy Duty Diesel), whichever comes first. While deleterious effects are not expected to be significant, mixing with conventional coolants will result in a lower than expected lifetime.

Product should be stored in original container or appropriate dedicated tank or vessel. Although temperature fluctuations will not adversely affect coolant, unused coolant should be stored at ambient conditions. Under typical conditions and when the container integrity is maintained, product can be stored for up to 2 years without any adverse effect on quality. Product should be agitated before use.

	Concentrate	50/50
Universal Oil MSDS / Item Number	16-42-15	16-42-16

Always consult your vehicles owner manual for proper fluid recommendations and flushing procedures.

The statements, technical information and recommendations contained herein are reliable, but given without warranty or guarantee of any kind. We assume no responsibility for loss, damage or expense, direct or consequential, arising out of the use of, or inability to use, our goods.