



265 Jefferson Avenue • Cleveland, Ohio 44113-2594
(216) 771-4300 • Ohio WATS (800) 362-1530
Fax (216) 771-1845

Product Information

Page 1 of 1

ALUMINUM COMPLEX EP-2 lubricating Grease

Product Description

Aluminum Complex EP-2 is a premium lubricating grease formulated with medium/high viscosity virgin base oils, and fortified with a special additive package which insures high film strength, extreme pressure (EP) and anti-wear properties. Aluminum Complex EP-2 has been fortified with oxidation as well as corrosion inhibitors and has excellent water resistance.

Specifications

NLGI Grade	2
Soap Type	Aluminum Complex
Texture	Smooth
Color.....	Dark Amber
Worked Penetration, ASTM D 217, 77°F, 60 Strokes.....	265-295
Dropping Point, ASTM D 2265, °F (CE) Min	500 (260)
Oxidation Stability, ASTM D 942, psi Drop 100 Hrs Max	5
Wheel Bearing Leakage, ASTM D 1263 Gms.....	5
Rust & Corrosion, ASTM D 1743	Pass
Water Washout, ASTM D 1264, 175°F	5%
Timken, ASTM D 2509, OK Load	45
Four Ball EP, ASTM D 2596	
Weld Point Kg.....	315
LWI.....	40
Four Ball Wear, ASTM D 2266	
Scar Dia. mm, 40 Kg.....	0.60
Base Oil Viscosity	
SUS @ 100°F,	1000-1250
cSt @ 100°C,.....	14.5-16.5
cSt @ 40°C,.....	180-220
Viscosity Index.....	70 Min
Pour Point °F.....	0

Refer to Universal Oil's Material Safety Data Sheet (MSDS) [18 41-01A](#), [02A](#) for additional information.