



265 Jefferson Avenue • Cleveland, Ohio 44113-2594
(216) 771-4300 • Ohio WATS (800) 362-1530
Fax (216) 771-1845

Product Information

Page 1 of 1

OIL DC 110

Test Description	Test Method	Typicals
• Viscosity, SUS @ 100° F	ASTM D 2161	108
Viscosity, SUS @ 210° F	ASTM D 2161	40.0
• Viscosity cSt @ 40° C	ASTM D 445	20.52
Viscosity, cSt @ 100° C	ASTM D 445	4.07
A.P.I. Gravity @ 60° F	ASTM D 1298	32.2
• Specific Gravity @ 60° F	ASTM D 1298	0.8640
• Weight, lbs/gal	ASTM D 1250	7.20
Flash Point, COC ° F	ASTM D 92	395
Color, ASTM	ASTM D 1500	1.0
Pour Point ° F	ASTM D 97	0
Aniline Point, ° F	ASTM D 611	212
Sulfur, wt %	ASTM D 2622	0.001
• Water Content	STM #6	Pass
• Appearance	STM #7	Pass

- **Test Data Supplied on Certificate of Analysis**

Refer to Universal Oil's Material Safety Data Sheet (MSDS) 18-32-01 for additional information.

The statements, technical information and recommendations contained herein are reliable, but given without warranty or guarantee of any kind. We assume no responsibility for loss, damage or expense, direct or consequential, arising out of the use of, or inability to use, our goods.