



265 Jefferson Avenue • Cleveland, Ohio 44113-2594  
(216) 771-4300 • Ohio WATS (800) 362-1530  
Fax (216) 771-1845

Product Information

Page 1 of 1

## OIL GRIND 710

### Product Description

**OIL Grind 710** is a low viscosity grinding fluid that provides faster chip settling, easy filtration and excellent cooling ability. The product is built with paraffinic base stock to resist oxidation and combines sulfur and fat to provide extreme pressure and lubricating properties. The product will provide good wheel life, impart good surface finish and improve bath longevity.

### Benefits

- Anti-weld properties
- Increase wheel life
- Low smoke generation
- Enhanced lubricating properties
- Good surface finish

### Typical Specifications

Appearance	Clear/Dark
Viscosity cSt @ 100°F	19.32 – 25.15
Viscosity SUS @ 100°F	95 – 120
A.P.I. Gravity @ 60°F	32.0
Wt./Gallon	7.20
Flash °F	350 min.
Sulfur	Present
Fat	Present

Refer to Universal Oil's Material Safety Data Sheet (MSDS) **18-28-08** for additional information.  
Universal Oil Item Number: 18 28 08

*The statements, technical information and recommendations contained herein are reliable, but given without warranty or guarantee of any kind. We assume no responsibility for loss, damage or expense, direct or consequential, arising out of the use of, or inability to use, our goods.*