



265 Jefferson Avenue • Cleveland, Ohio 44113-2594
(216) 771-4300 • Ohio WATS (800) 362-1530
Fax (216) 771-1845

Product Information

Page 1 of 1

OIL KUT 220

Product Description

OIL Kut 220 is a light colored, low viscosity cutting fluid that provides faster chip settling, easy filtration and excellent cooling capability. The product is built with paraffinic base stock to resist oxidation and it combines sulfur, chlorine and fat to provide extreme pressure and boundary lubricating properties. The light viscosity of **OIL Kut 220** will dissipate heat quickly and minimize carry-out on parts. The product contains active sulfur, which can stain copper, and it's alloys and should not be used to machine these metals.

Benefits

- Light in color for better operator acceptance
- High film strength characteristics
- Anti-weld properties
- Enhanced lubricating properties
- Increased tool life
- Good surface finish
- Good heat transfer properties

Typical Specifications

Appearance	Clear / Amber
Viscosity cSt @ 100°F	27.5
Viscosity SUS @ 100°F	130
Wt./Gal	7.30
Flash °F	370 min.
Sulfur	Present
Chlorine	Present
Fat	Present

Refer to Universal Oil's Material Safety Data Sheet (MSDS) **18-28-33** for additional information.
Universal Oil, Inc. Item Number 18-28-33

The statements, technical information and recommendations contained herein are reliable, but given without warranty or guarantee of any kind. We assume no responsibility for loss, damage or expense, direct or consequential, arising out of the use of, or inability to use, our goods.