



265 Jefferson Avenue • Cleveland, Ohio 44113-2594
(216) 771-4300 • Ohio WATS (800) 362-1530
Fax (216) 771-1845

Product Information

Page 1 of 1

OIL KUT 444

Product Description **Oil Kut 444** is a heavy-duty multipurpose cutting oil. The product combines sulfur, chlorine and a lubricity package to provide extreme pressure and boundary lubricant properties. It provides good tool life, imparts good finish and exhibits excellent oxidation stability. **OIL Kut 444** contains active sulfur which can stain copper and its alloys and should not be used to machine these metals.

Applications **Oil Kut 444** is recommended for most metal removing operations such as thread, grinding, tapping, turning and cutting on metals ranging from free machining to high alloy steels.

- Benefits**
- Versatile cutting oil for wide range of applications
 - Enhanced lubricity properties
 - Good surface finish
 - Excellent EP and anti-weld properties
 - Increased tool life
 - Low smoke

Typical Specifications

Appearance	Clear/Dark
Viscosity cSt @ 100 °F	35.20
Viscosity SUS @ 100 °F	164.9
A.P.I. Gravity @ 60 °F	30.0
Wt/Gal	7.3
Flash °F	370 min.
Sulfur	Present
Chlorine	Present
Fat	Present

*Refer to Universal Oil's Material Safety Data Sheet (MSDS) 18 28 12 for additional information.
Universal Oil Item Number 18 28 12*

The statements, technical information and recommendations contained herein are reliable, but given without warranty or guarantee of any kind. We assume no responsibility for loss, damage or expense, direct or consequential, arising out of the use of, or inability to use, our goods.