



265 Jefferson Avenue • Cleveland, Ohio 44113-2594
(216) 771-4300 • Ohio WATS (800) 362-1530
Fax (216) 771-1845

Product Information

Page 1 of 1

OIL KUT 600

Product Description

OIL KUT 600 is a heavy-duty sulfur-chlorinated cutting oil designed for severe cutting operations on low machinability metals ($\leq 50\%$), primarily stainless steel applications. **OIL KUT 600** combines sulfur, fat and chlorine to provide tool wear protection and better surface finish capabilities. The extreme pressure properties working synergistically promote a low coefficient of friction through a wide temperature range. The formulation is compounded with active sulfur and it will stain yellow metals.

Benefits

- Removed easily with alkaline or solvent cleaning
- Excellent surface finish
- Enhanced Extreme Pressure additive package
- Increased tool life

Typical Specifications

Appearance	Clear / Light
Viscosity cSt @ 100°F	40.00
Viscosity SUS @ 100°F	190
A.P.I. Gravity @ 60°F	8.4
Wt. / Gal	8.4
Flash °F	320 min.
Sulfur (active)	present
Chlorine	present
Fat	present

*Refer to Universal Oil's Material Safety Data Sheet (MSDS) 18-28-35 for additional information.
Universal Oil Item Number: 18-28-35.*

The statements, technical information and recommendations contained herein are reliable, but given without warranty or guarantee of any kind. We assume no responsibility for loss, damage or expense, direct or consequential, arising out of the use of, or inability to use, our goods.