



265 Jefferson Avenue • Cleveland, Ohio 44113-2594
(216) 771-4300 • Ohio WATS (800) 362-1530
Fax (216) 771-1845

Product Information

Page 1 of 1

#2 PREMIUM DIESEL ULTRA LOW SULFUR - DYED

Specifications

Typical Property	Typical Results
Gravity, °API	39° Maximum
Flash, °F	125° Minimum
Viscosity @ 100°F, cSt	2.4 - 3.95
Color	Dyed
Cloud Point, °F	+5° Maximum
Sulfur, wt., ppm	15 Maximum
Corrosion	1
BTU/Gallon	142,000 Typical
Calculated Cetane Index	50 Maximum
Distillation, °F	
10%	460° Maximum
50%	475° Minimum
90%	525° - 580°
Final Boiling Point	625° Maximum
Pour Point, °F	-10° Maximum
Carbon Residue, Ramsbottom 10% Bottoms	0.25 Maximum
BS&W	0.05 Maximum
MSDS Number	10-31-01

- Multifunctional Premium Diesel Additive
- Exceeds Cummins L-10 Injector Cleanliness Requirements and Cummins L-14 Injector Wear Requirements

Also known as: Marine Gas Oil
Off Road Diesel
#2 Heating Oil