



265 Jefferson Avenue • Cleveland, Ohio 44113-2594
(216) 771-4300 • Ohio WATS (800) 362-1530
Fax (216) 771-1845

Product Information

Page 1 of 1

PARPREME 500

Product Description Parpreme 500 is a paraffinic process oil, severely hydrotreated, that provides excellent product stability and low volatility.

Specification	Typical Value
API Gravity @60°F	30.2
Specific Gravity @60°F	0.8751
Density Lbs.	7.287
Vis, SUS @100°F	501.1
Vis, SUS @210°F	65.0
Vis, cSt @40°C	96.332
Vis, cSt @100°C	11.305
Viscosity Index	104
Viscosity-Gravity Constant	0.8024
Flash Point, COC, °F	455
Flash Point, COC, °C	235.0
Color, ASTM	2.5
Pour Point, °F	10
Pour Point, °C	-12.2
Sulfur, wt%	0.0046
Sulfur, ppm	46
UVA @260 nm	1.14
Refractive Index, 20°C	1.4810
Aniline Point, °F	246.2
Asphaltene Content, wt%	0
Polar Content, wt%	0.9
Aromatic Content, wt%	13
Saturate Content, wt%	86.1
Noack Evaporative Loss, wt%	10.2

Universal Oil Item Number 18 32 19

Refer to Universal Oil's Material Safety Data Sheet (MSDS) **18-32-09** for additional information.

The statements, technical information and recommendations contained herein are reliable, but given without warranty or guarantee of any kind. We assume no responsibility for loss, damage or expense, direct or consequential, arising out of the use of, or inability to use, our goods.