

**MATERIAL SAFETY DATA SHEET**

**INHIBITED PROPYLENE GLYCOL - PINK**

Latest Revision Date...11/04/10

Print Date.....04/05/11

**SECTION 1 MANUFACTURER INFORMATION**

UNIVERSAL OIL, INC.  
265 JEFFERSON AVENUE  
CLEVELAND, OHIO 44113  
TELEPHONE: 216-771-4300 FAX: 216-771-1845

**SECTION 2 PRODUCT IDENTIFICATION**

PRODUCT NUMBER..... UO PGI-P  
TRADE NAME OR CHEMICAL NAME... INHIBITED PROPYLENE GLYCOL - PINK  
SYNONYMS..... NA  
CHEMICAL FAMILY..... Antifreeze  
NFPA - HEALTH HAZARD..... 1  
FIRE HAZARD..... 1  
REACTIVITY HAZARD..... 0  
NFPA SCALE..... 4=Extreme 3=High 2=Moderate 1=Slight 0=Insignificant  
KEY..... NA= Not Applicable ND= Not Determined

**SECTION 3 HAZARDOUS INGREDIENTS**

CHEMICAL NAME(S)	CAS NUMBER	% WT	TLV-TWA	PEL	SEC.313	CARCINOGEN?
None	NA	-	NA	NA	No	NA

**SECTION 4 SHIPPING DATA**

D.O.T. PROPER SHIPPING NAME... NA  
D.O.T. HAZARD CLASS..... NA  
D.O.T. LABELS REQUIRED..... NA  
UN/NA I.D. NUMBER..... NA  
PACKAGING GROUP..... NA  
NON-BULK SHIPPING NAME..... Compounds, Anti-freezing, Liquid  
BULK SHIPPING NAME..... Same

**SECTION 5 PHYSICAL DATA**

BOILING/FREEZING POINT @760 mmHg... 370°F (188°C) / -40°F (-40°C)  
pH..... 9.5 (50% Solution)  
VAPOR PRESSURE mm Hg @20° C..... 0.22  
VAPOR DENSITY (Air = 1)..... 2.62  
PERCENT VOLATILE BY WEIGHT (%)..... <5  
SPECIFIC GRAVITY @20°C..... 1.05  
SOLUBILITY IN WATER..... Complete  
EVAPORATION RATE..... (Water=1) <1  
APPEARANCE AND ODOR..... Pink liquid with faint odor.

**SECTION 6 FIRE AND EXPLOSION HAZARD DATA**

FLASH POINT (Test Method)..... 212°F (102°C) T.O.C.  
AUTOIGNITION TEMPERATURE..... ND  
FLAMMABILITY LIMITS IN AIR (% V)... LFL: 2.6% @ 100°C, UFL: 12.5% @ 130°C

INHIBITED PROPYLENE GLYCOL - PINK

SECTION 6

FIRE AND EXPLOSION HAZARD DATA

CONT'D

EXTINGUISHING MEDIA..... Water fog, dry chemical, carbon dioxide  
SPECIAL FIRE FIGHTING PROCEDURES... Wear full protective clothing and self-contained breathing apparatus.  
UNUSUAL FIRE & EXPLOSION HAZARDS... Cool drums to prevent rupture.

SECTION 7

REACTIVITY DATA

PRODUCT STABILITY..... Stable over normal temperature range -30°F to 250°F  
Conditions to Avoid..... NA  
CHEMICAL INCOMPATIBILITY..... Strong oxidizers  
HAZARDOUS DECOMPOSITION PRODUCTS... During combustion- carbon monoxide, carbon dioxide and unidentified organic compounds  
HAZARDOUS POLYMERIZATION..... Will Not Occur

SECTION 8

HEALTH HAZARD DATA

SKIN CONTACT... Extended contact may cause skin irritation in extremely sensitive people.  
EYE CONTACT.... May cause irritation.  
INHALATION.... Irritation unlikely, but avoid inhalation.  
INGESTION..... Irritation unlikely, do not ingest.

SECTION 9

EMERGENCY AND FIRST AID PROCEDURES

SKIN.....Wash exposed skin with soap and water. Launder contaminated clothing before reuse.  
EYES.....Promptly flush eyes with large amounts of water. Get medical attention if any discomfort persists.  
INGESTION...If swallowed, DO NOT INDUCE VOMITING. Get medical attention. Never give anything by mouth to an unconscious person.  
INHALATION...Move to fresh air. Get medical attention if indicated.

SECTION 10

ENVIRONMENTAL DATA

SPILL OR LEAK PROCEDURES... Absorb onto inert material and place in suitable containers for disposal. Do not flush directly into open waterways.  
WASTE DISPOSAL METHOD..... Dispose of in accordance with all federal, state and local regulations.  
HAZARDOUS WASTE 40CFR261... NA  
CONTAINER DISPOSAL..... Empty containers may contain residuals. Thoroughly clean, then offer for recycling , reuse, or disposal in accordance with governmental regulations.

SECTION 11

SPECIAL PROTECTION INFORMATION

RESPIRATORY PROTECTION.....Respirator not required with most applications.  
VENTILATION.....Local exhaust is generally sufficient to minimize exposure.  
PROTECTIVE CLOTHING.....Neoprene gloves, apron, boots - as necessary to prevent skin contact.  
EYE PROTECTION.....Chemical goggles.  
OTHER PRECAUTIONS.....Safety shower and eyewash fountains should be easily accessible.

SECTION 12

SUPPLIER INFORMATION

This information is furnished without warranty, expressed or implied, except that it is accurate to the best knowledge of manufacturer. The data on this sheet relates only to the specific material designated herein. Manufacturer assumes no legal responsibility for use or reliance upon this data.