



265 Jefferson Avenue • Cleveland, Ohio 44113-2594
(216) 771-4300 • Ohio WATS (800) 362-1530
Fax (216) 771-1845

Product Information

Page 1 of 1

UNIVERSAL SLUSHING OIL

Product Description

Universal Slushing Oil is predominantly paraffinic type neutral oil. It is also suitable for various process applications where high flash point paraffin oils are desired, and blends readily with hydrocarbons and chemicals.

Applications

Universal Slushing Oil is recommended for use in a wide range of applications such as:

- Flushing and cleaning oil
- Quenching oil in steel heat treatment
- Rust preventive
- Stamping lubricant in thin gage metal

Specifications

Typical Property	Test Method	Typical Results
ISO Grade		22
Gravity API @ 60°F	ASTM D 287	33
Viscosity, cSt @ 40°C	ASTM D 445	19.3
SUS @ 100°F	ASTM D 2161	95.0
SUS @ 210°F	ASTM D 2161	38.8
Viscosity Index	ASTM D 2270	93
Pour Point	ASTM D 97	+10°
Flash Point, F	ASTM D 92	390°
Color ASTM	ASTM D 1500	1
Neut. No. mg KOH/g		.01
Aniline No. F		193
Carbon Residue, wt %		.05

Universal Oil Item Number

16-21-01

Refer to Universal Oil's Material Safety Data Sheet (MSDS) [16-03-01\(Universal Mineral Oil\)](#) for additional information.