



265 Jefferson Avenue • Cleveland, Ohio 44113-2594  
(216) 771-4300 • Ohio WATS (800) 362-1530  
Fax (216) 771-1845

Product  
Information

Page 1 of 2

## UNIVERSAL FS DEXOS GEN II 5W30 MOTOR OIL

<b>Product Description</b>	<b>UNIVERSAL FS DEXOS GEN II 5W30 MOTOR OIL</b> Full Synthetic 5W-30 Motor Oil meet or exceed GM dexos1™ Gen 2 specifications for worldwide warranty requirements for all GM automotive gasoline engines currently in use. The oils are fully licensed by GM	
<b>Applications</b>	Gasoline-fueled and flex-fuel passenger cars, light trucks and sport utility vehicles, including gasoline-electric hybrids, especially when operating under severe conditions. Formulated to protect turbochargers and emission control system catalysts. Formulated for use in vehicles operating on ethanol-containing fuels up to E85	
<b>OEM SPEC'S</b>	API SN Approved API SN Plus Approved dexos1® Gen2 Approved ILSAC GF-5 Approved API SJ, SH, SG, SF Meets Requirements API SL Meets Requirements	API SM Meets Requirements Chrysler MS-6395 Meets Requirements Ford WSS M2C946-A, M2C929-A Meets Requirements GM 4718M Meets Requirements GM 6094M Meets Requirements ILSAC GF-4 Meets Requirements
<b>Benefits</b>	Improved fuel economy. Reduces fuel costs without sacrificing engine protection and performance. Also improves acceleration. Extended oil drain intervals. Engineered to handle the most extreme conditions. 100% pure synthetic oils. Contains uniform molecules that provide the best, longest-lasting engine protection and performance.	

**UNIVERSAL FS DEXOS GEN II 5W30 MOTOR OIL****Specifications****Typical Property****Typical Results****5W30**

## Viscosity

@ 40° C, cSt

62

@ 100° C, cSt

11

CCS, cP

4400 (-30)

Index

169

Pour Point °F

-49

Flash Point °F

441

Color

3

Total Base No.

7.9

Universal Oil Item No

160411